



- NOTES:
1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. 1K=1K10 OHM, M=MEG OHM.
 2. RESISTOR WATTAGES ARE 1/5W UNLESS OTHERWISE NOTED.
 3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (P=PICTO MICRO FARAD)
 4. ALL CAPACITORS TEMPERATURE CHARACTERISTICS ARE 2% UNLESS OTHERWISE NOTED.
 5. ALL CAPACITORS TEMPERATURE CHARACTERISTICS ARE 5% (LESS THAN 100PF) OR 2% (MORE THAN 100PF) UNLESS OTHERWISE NOTED.
 6. CHIP PARTS ARE NOT SPECIFIED IN THIS SCHEMATIC DIAGRAM. PLEASE REFER TO THE PARTS LIST FOR THE CHIP PARTS.
 7. VOLTAGE IN □ SHOWS TX CONDITION.
 8. VOLTAGE IN ▽ SHOWS RX CONDITION UNDER OPERATION OF EACH FUNCTION.
 9. VOLTAGE IN ○ MARK SHOWS RX CONDITION.